



### Dimensions

|                  |          |
|------------------|----------|
| Weight:          | 5 lbs    |
| Internal Length: | 12.00 in |
| Internal Width:  | 9.00 in  |
| Internal Height: | 4.50 in  |
| External Length: | 13.18 in |
| External Width:  | 11.12 in |
| External Height: | 5.21 in  |
| Lid Height:      | 1.50 in  |
| Bottom Depth:    | 3.00 in  |

### Features

Injection Molded Case

Waterproof and dust tight design (MIL-C-4150J)

Molded-in hinge for added protection

Trigger release latch system

Snap-down rubber over-molded cushion grip handle

Ambient pressure equalization valve (MIL-STD-648C)

Resistant to UV, solvents, corrosion, fungus (MIL-STD-810F)

Resistant to impact damage (MIL-STD-810F)

## Variations

SKB iSeries 1209-4 Case - Cubed Foam

SKB iSeries 1209-4 Case - Layered Foam

SKB iSeries 1209-4 Case - Empty

## All Options and Accessories

Locking Latch Kit (\$24.00)

Panel Mount Clip Kit (\$22.00)

## Certificates and Downloads

[Certified 3I Series Waterproof Test](#)

[Certified 3I Series Drop Test](#)

[3I-1209-4 Dimensional Drawing](#)

[SKB Pelican Comparison Size Chart](#)