



## Dimensions

|                  |          |
|------------------|----------|
| Weight:          | 24 lbs   |
| Internal Length: | 22.00 in |
| Internal Width:  | 17.00 in |
| Internal Height: | 12.75 in |
| External Length: | 24.34 in |
| External Width:  | 19.47 in |
| External Height: | 14.38 in |
| Lid Height:      | 2.00 in  |
| Bottom Depth:    | 10.75 in |

## Features

Injection Molded Case with wheels and industrial strength pull handle

Waterproof and dust tight design (MIL-C-4150J)

Molded-in hinge for added protection

Trigger release latch system and padlock holes

Snap-down rubber over-molded cushion grip handle

Ambient pressure equalization valve (MIL-STD-648C)

Resistant to UV, solvents, corrosion, fungus (MIL-STD-810F)

Resistant to impact damage (MIL-STD-810F)

## Variations

SKB iSeries 2217-12 Case - Empty

SKB iSeries 2217-12 Case - Cubed Foam

## All Options and Accessories

Panel Mount Clip Kit (\$22.00)

Locking Latch Kit (\$24.00)

## Certificates and Downloads

[Certified 3I Series Waterproof Test](#)

[Certified 3I Series Drop Test](#)

[3I-2217-12 Dimensional Drawing](#)

[SKB Pelican Comparison Size Chart](#)