



## Dimensions

|                  |          |
|------------------|----------|
| Weight:          | 27 lbs   |
| Internal Length: | 42.50 in |
| Internal Width:  | 17.00 in |
| Internal Height: | 7.52 in  |
| External Length: | 45.12 in |
| External Width:  | 19.45 in |
| External Height: | 8.34 in  |
| Lid Height:      | 2.00 in  |
| Bottom Depth:    | 5.52 in  |

## Features

Injection Molded Case with wheels

Waterproof and dust tight design (MIL-C-4150J)

Molded-in hinge for added protection

Trigger release latch system

Snap-down rubber over-molded cushion grip handle

Ambient pressure equalization valve (MIL-STD-648C)

Resistant to UV, solvents, corrosion, fungus (MIL-STD-810F)

Resistant to impact damage (MIL-STD-810F)

## Variations

SKB iSeries 4217-7 Case - Empty

SKB iSeries 4217-7 Case - Layered Foam

## All Options and Accessories

Panel Mount Clip Kit (\$22.00)

Locking Latch Kit (\$24.00)

## Certificates and Downloads

[Certified 3I Series Waterproof Test](#)

[Certified 3I Series Drop Test](#)

[3I-4217-7 Dimensional Drawing](#)

[SKB Pelican Comparison Size Chart](#)