



Dimensions

| | |
|------------------|--------------|
| Weight: | 62 lbs |
| Internal Length: | 24.00 in |
| Internal Width: | 19.00 in |
| Internal Height: | 5.25 in |
| External Length: | 39.05 in |
| External Width: | in |
| External Height: | in |
| Lid Height: | 2 (Front) in |
| Bottom Depth: | in |

Features

SKB Lifetime Warranty
Pressure relief valve
Recessed black powder coated stainless steel hardware
Completely removable frame
Front doors are 2" deep, Rear doors are 5" deep
Standard Rack depth 24" rail to rail
Standard 19" Rack width per ANSI/EIA-310-C
Molded in stacking ribs and lugs
8 comfort grip spring loaded lift handles
Rotationally molded case
Case coupling straps and lid hangers
Meets or exceeds MIL-STD 810G
Square hold rack rails to accommodate either #10-32 US standard, or 6mm int. standard cage nuts

All Options and Accessories

Small Access. Pocket - Uninstalled (20"x10"x 3") (\$84.99)

Caster Accessory Bag (\$94.99)

Shipping Label Plate (\$34.99)

40 - 150 lbs. (\$0.00)

150+ lbs. - Contact Allcases for Assistance Before Ordering (\$0.00)

Certificates and Downloads

[RESK-3RR-3U24-25B](#)

[SKB 3RR Sliding Rack Case](#)