



## Dimensions

|                  |              |
|------------------|--------------|
| Weight:          | 90 lbs       |
| Internal Length: | 24.00 in     |
| Internal Width:  | 19.00 in     |
| Internal Height: | 19.25 in     |
| External Length: | in           |
| External Width:  | in           |
| External Height: | in           |
| Lid Height:      | 2 (Front) in |
| Bottom Depth:    | in           |

## Features

SKB Lifetime WarrantyPressure relief valveRecessed black powder coated stainless steel hardwareCompletely removable frameFront doors are 2" deep, Rear doors are 5" deepStandard Rack depth 24" rail to rail Standard 19" Rack width per ANSI/EIA-310-C Molded in stacking ribs and lugs8 comfort grip spring loaded lift handlesRotationally molded caseCase coupling straps and lid hangersMeets or exceeds MIL-STD 810G Square hold rack rails to accommodate either #10-32 US standard, or 6mm int. standard cage nuts

## All Options and Accessories

Small Access. Pocket - Uninstalled (20"x10"x 3") (\$84.99)

Large Access. Pocket - Uninstalled (20"x15"x3") (\$94.99)

Caster Accessory Bag (\$94.99)

Shipping Label Plate (\$34.99)

40 - 150 lbs. (\$0.00)

150+ lbs. - Contact Allcases for Assistance Before Ordering (\$0.00)

## Certificates and Downloads

[RESK-3RR-11U24-25B](#)

[SKB 3RR Sliding Rack Case](#)