



Dimensions

Weight:	77 lbs
Internal Length:	31.00 in
Internal Width:	19.00 in
Internal Height:	19.25 in
External Length:	39.05 in
External Width:	23.80 in
External Height:	25.84 in
Lid Height:	2 (Front) in
Bottom Depth:	in

Features

SKB Lifetime Warranty
 Pressure relief valve
 Recessed black powder coated stainless steel hardware
 Front doors are 2" deep, Rear doors are 5" deep
 Standard Rack depth 24" rail to rail
 Standard 19" Rack width per ANSI/EIA-310-C
 Molded in stacking ribs and lugs
 8 comfort grip spring loaded lift handles
 Rotationally molded case
 Case coupling straps and lid hangers
 Meets or exceeds MIL-STD 810G
 Square hold rack rails to accommodate either #10-32 US standard, or 6mm int. standard cage nuts

All Options and Accessories

Small Access. Pocket - Uninstalled (20"x10"x 3") (\$84.99)

Large Access. Pocket - Uninstalled (20"x15"x 3") (\$94.99)

Shipping Label Plate (\$34.99)

Caster Accessory Bag (\$94.99)

40 - 150 lbs. (\$0.00)

150+ lbs. - Contact Allcases for Assistance Before Ordering (\$0.00)

Certificates and Downloads

[RESK-3RS-11U24-25B](#)

[SKB 3RS Static Rack Case](#)