



Dimensions

|                  |          |
|------------------|----------|
| Weight:          | 37 lbs   |
| Internal Length: | 22.5 in  |
| Internal Width:  | 21.06 in |
| Internal Height: | 23.62 in |
| External Length: | 25.5 in  |
| External Width:  | 0 in     |
| External Height: | 25.31 in |
| Lid Height:      | 19.62 in |
| Bottom Depth:    | 4 in     |

Features

Rotationally Molded Case  
Molded-in Flange to support panel mounted gear  
One-piece construction  
Reinforced corners and edges for extra impact protection  
Molded-in, tongue-in-groove gasketed parting lines  
Comfort Grip handles  
Molded-in ribs and corrugations for secure, non-slip stacking  
Recessed hardware  
Positive anti-shear locks that prevent lid separation after impact  
Molded-in metal inserts for catch and hinge attachment points

## All Options and Accessories

Standard Color (\$0.00)

Tan (\$14.00)

Black (\$14.00)

All Fed.Std Colors Available (\$14.00)

Olive Drab (OD Green) (\$14.00)

No Foam (\$0.00)

2" Foam Lined (\$158.00)

Foam Filled (\$198.00)

No Lock (\$0.00)

Lockable Cable Catch (each) (\$38.00)

Zinc Hardware w/Plastic Handles (Standard) (\$0.00)

Stainless Steel Hardware w/Stainless Steel Handles (\$71.00)

Zinc Hardware w/Zinc Handles (\$6.00)

Stainless Steel Hardware w/Plastic Handles (\$62.00)

Air Tight Construction Breather Valve (Manual) (\$63.00)

## Certificates and Downloads

[Pelican-Hardigg Single Lid Testing Cert](#)

[Pelican-Hardigg Single Lid Brochure](#)