



# Material Safety Data Sheet

The Dow Chemical Company

**Product Name:** ETHAFOAM\* 220 A/S Pink Polyethylene Foam Plank

**Issue Date:** 06/13/2007

**Print Date:** 14 Jun 2007

The Dow Chemical Company encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

## 1. Product and Company Identification

### Product Name

ETHAFOAM\* 220 A/S Pink Polyethylene Foam Plank

### COMPANY IDENTIFICATION

The Dow Chemical Company  
2030 Willard H. Dow Center  
Midland, MI 48674  
USA

Customer Information Number: 800-258-2436

### EMERGENCY TELEPHONE NUMBER

**24-Hour Emergency Contact:** 989-636-4400

**Local Emergency Contact:** 989-636-4400

## 2. Hazards Identification

### Emergency Overview

**Color:** Pink

**Physical State:** Foam

**Odor:** Odorless

**Hazards of product:**

No significant immediate hazards for emergency response are known.

### OSHA Hazard Communication Standard

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### Potential Health Effects

**Eye Contact:** Solid or dust may cause irritation or corneal injury due to mechanical action.

Fumes/vapor released during thermal operations such as hot-wire cutting may cause eye irritation.

**Skin Contact:** Prolonged contact may cause slight skin irritation with local redness.

**Skin Absorption:** Skin absorption is unlikely due to physical properties.

\* Indicates a Trademark

**Inhalation:** Dust may cause irritation to upper respiratory tract (nose and throat). Fumes/vapors released during thermal operations such as hot wire cutting may cause respiratory irritation.  
**Ingestion:** Swallowing is unlikely because of the physical state. Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts. May cause choking or blockage of the digestive tract if swallowed.

### 3. Composition Information

Component	CAS #	Amount
Ethene, homopolymer	9002-88-4	> 98.0 %

### 4. First-aid measures

**Eye Contact:** Flush eyes with plenty of water; remove contact lenses after the first 1-2 minutes then continue flushing for several minutes. Only mechanical effects expected. If effects occur, consult a physician, preferably an ophthalmologist.  
**Skin Contact:** Wash skin with plenty of water.  
**Inhalation:** Move person to fresh air; if effects occur, consult a physician.  
**Ingestion:** If swallowed, seek medical attention. May cause gastrointestinal blockage. Do not give laxatives. Do not induce vomiting unless directed to do so by medical personnel.  
**Notes to Physician:** No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

### 5. Fire Fighting Measures

**Extinguishing Media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam.  
**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Soak thoroughly with water to cool and prevent re-ignition. If material is molten, do not apply direct water stream. Use fine water spray or foam. Cool surroundings with water to localize fire zone. Hand held dry chemical or carbon dioxide extinguishers may be used for small fires.  
**Special Protective Equipment for Firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.  
**Unusual Fire and Explosion Hazards:** Mechanical cutting, grinding or sawing can cause formation of dusts. To reduce the potential for dust explosion, do not permit dust to accumulate. Dense smoke is emitted when burned without sufficient oxygen.  
**Hazardous Combustion Products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. In smoldering or flaming conditions, carbon monoxide, carbon dioxide and carbon are generated. Based on combustion toxicity testing, the effects of combustion from this foam are not more acutely toxic than the effects of combustion from common building materials such as wood.

### 6. Accidental Release Measures

**Steps to be Taken if Material is Released or Spilled:** Recover spilled material if possible. See Section 13, Disposal Considerations, for additional information.  
**Personal Precautions:** There are no special required instructions.  
**Environmental Precautions:** There are no special required instructions.

## 7. Handling and Storage

### Handling

**General Handling:** Mechanical cutting, grinding or sawing can cause formation of dusts. To reduce the potential for dust explosion, do not permit dust to accumulate. This product is combustible and may constitute a fire hazard if improperly used or installed.

### Storage

Store in a cool, dry place. Keep away from high temperatures and hot pipes. Store away from direct sunlight. This material is combustible and should not be exposed to flame or other ignition sources.

## 8. Exposure Controls / Personal Protection

### Exposure Limits

None established

### Personal Protection

**Eye/Face Protection:** Eye protection should not be necessary. For fabrication operations safety glasses are recommended. If there is a potential for exposure to particles which could cause eye discomfort, wear chemical goggles.

**Skin Protection:** Wear clean, body-covering clothing.

**Hand protection:** Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use gloves to protect from mechanical injury. Selection of gloves will depend on the task. Examples of preferred glove barrier materials include: Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Respiratory Protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. When respiratory protection is required for certain operations, including but not limited to saw, router or hot-wire cutting, use an approved air-purifying respirator. In dusty or misty atmospheres, use an approved particulate respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

**Ingestion:** No precautions necessary due to the physical properties of the material.

### Engineering Controls

**Ventilation:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

## 9. Physical and Chemical Properties

Physical State	Foam
Color	Pink
Odor	Odorless
Flash Point - Closed Cup	340 °C (644 °F) <i>Literature</i>
Flammable Limits In Air	<b>Lower:</b> Not applicable <b>Upper:</b> Not applicable

<b>Autoignition Temperature</b>	3,350 °C (6,062 °F) <i>Literature</i>
<b>Vapor Pressure</b>	Not applicable
<b>Boiling Point (760 mmHg)</b>	Not applicable.
<b>Vapor Density (air = 1)</b>	Not applicable
<b>Specific Gravity (H2O = 1)</b>	<i>Not applicable</i>
<b>Liquid Density</b>	25 - 65 g/cm <sup>3</sup>
<b>Freezing Point</b>	Not applicable
<b>Melting Point</b>	< 150 °C (< 302 °F) <i>Estimated</i>
<b>Solubility in Water (by weight)</b>	insoluble in water
<b>pH</b>	Not applicable
<b>Kinematic Viscosity</b>	Not applicable

## 10. Stability and Reactivity

### Stability/Instability

Thermally stable at typical use temperatures.

**Conditions to Avoid:** Avoid temperatures above 70 °C (158 °F). Product decomposes above: 250 °C (482 °F). Avoid direct sunlight.

**Incompatible Materials:** Avoid contact with: Strong oxidizers.

### Hazardous Polymerization

Will not occur.

### Thermal Decomposition

Decomposition products depend upon temperature, air supply and the presence of other materials. Processing may release fumes and other decomposition products. At temperatures exceeding melt temperatures, polymer fragments can be released. Fumes can be irritating.

## 11. Toxicological Information

### Repeated Dose Toxicity

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

## 12. Ecological Information

### CHEMICAL FATE

#### Movement & Partitioning

No bioconcentration is expected because of the relatively high molecular weight (MW greater than 1000). In the terrestrial environment, material is expected to remain in the soil. In the aquatic environment, material is expected to float.

#### Persistence and Degradability

Surface photodegradation is expected with exposure to sunlight. No appreciable biodegradation is expected.

### ECOTOXICITY

Not expected to be acutely toxic to aquatic organisms.

### 13. Disposal Considerations

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. DOW HAS NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Landfill. Incinerator or other thermal destruction device. As a service to its customers, Dow can provide names of information resources to help identify waste management companies and other facilities which recycle, reprocess or manage chemicals or plastics, and that manage used drums. Telephone Dow's Customer Information Group at 1-800-258-2436 or 1-989-832-1556 (U.S.), or 1-800-331-6451 (Canada) for further details.

### 14. Transport Information

**DOT Non-Bulk**  
NOT REGULATED

**DOT Bulk**  
NOT REGULATED

**IMDG**  
NOT REGULATED

**ICAO/IATA**  
NOT REGULATED

*This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.*

### 15. Regulatory Information

#### **OSHA Hazard Communication Standard**

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### **Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312**

<b>Immediate (Acute) Health Hazard</b>	No
<b>Delayed (Chronic) Health Hazard</b>	No
<b>Fire Hazard</b>	No
<b>Reactive Hazard</b>	No
<b>Sudden Release of Pressure Hazard</b>	No

#### **Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313**

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

**Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:**

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

**Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Special Hazardous Substances List:**

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

**California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)**

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

**US. Toxic Substances Control Act**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

**CEPA - Domestic Substances List (DSL)**

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

## 16. Other Information

### Hazard Rating System

<b>NFPA</b>	<b>Health</b>	<b>Fire</b>	<b>Reactivity</b>
	0	1	0

### Recommended Uses and Restrictions

Cushion packaging. For industrial use. Dow recommends that you use this product in a manner consistent with the listed use. If your intended use is not consistent with Dow's stated use, please contact Dow's Customer Information Group.

### Revision

Identification Number: 50291 / 1001 / Issue Date 06/13/2007 / Version: 3.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

### Legend

N/A	Not available
W/W	Weight/Weight
OEL	Occupational Exposure Limit
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
ACGIH	American Conference of Governmental Industrial Hygienists, Inc.
DOW IHG	Dow Industrial Hygiene Guideline
WEEL	Workplace Environmental Exposure Level
HAZ DES	Hazard Designation
Action Level	A value set by OSHA that is lower than the PEL which will trigger the need for activities such as exposure monitoring and medical surveillance if exceeded.

*The Dow Chemical Company urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no*

*warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.*