

# NEVER GIVE UP HOPE.

Most people have a job. First responders have a calling. It takes guts and determination, but it also takes preparation and the right tools. Pelican can help with the kind of innovations that can give you the edge while working to save a life. Our revolutionary RALS units (Remote Area Lighting Systems) put up to 15 hrs of light on the scene, and kill the noise and fumes of generator based emergency lights. Our rugged cases transport support equipment from defibrillators to portable

X-ray machines, and arrive in mission critical situations ready to work.

Pelican manufactures a broad range of safety approved lights for hazardous areas. If the emergency includes a ruptured gas line or vapors from an open fuel spill, the wrong flashlight could become a source of ignition. We cover medical teams with hand-carry EMS cases and field hospital med chests, as well as portable field desks and foot lockers suitable for emergency command centers.

At Pelican we know first responders never give up. Neither should their gear. Haiti 2009- Trapped for 7 days, Kiki is pulled to safety by Task Force 1, a US search-and-rescue team.



# SEE OUR FULL LINE PELICAN.COM



PELICAN LIGHTING TOOLS Safety approved lights for hazardous areas

- Specialized lights for fire
- and rescue operations
- Submersible lights for diving
- Lightweight Rechargeable

Portable

Collapsible

# INJECTION MOLDED CASES

Pelican Products, Inc. guarantees its products for a lifetime against breakage or defects in workmanship. Pelican<sup>™</sup> injection molded cases are guaranteed to be watertight to a depth of 3.3 feet (1 meter) for 30 minutes (IP 67) if properly closed with undamaged o-ring in place unless otherwise stated. Pelican's liability is limited to the case and not its contents or foam. All warranty claims of any nature are barred if the container has been altered, damaged or in any way physically changed, or subjected to abuse, misuse, negligence or accident. Refer to www.pelican.com/warranty for full details.

# **ROTO MOLDED AND SPECIALTY CASES**

Pelican guarantees its Roto Molded cases for 1 year against defects in materials and workmanship and 90 days on hardware from the proof of purchase. All warranty claims of any nature are barred if the container has been altered, damaged or in any way physically changed, or subjected to abuse, misuse, negligence or accident. Refer to www.pelican.com/warranty for full details.

#### CALIFORNIA

23215 Early Avenue Torrance, CA 90505 Tel: 310 326 4700 • 800 473 5429 Fax: 310.326.3311 www.pelican.com

## MASSACHUSETTS

147 North Main Street South Deerfield, MA 01373 Tel: 800.542.7344 • Fax: 413.665.8330 www.pelican.com



# PELICAN



Advanced LED Technology



# PELICAN PROTECTOR CASES

- Over 70 sizes
- Watertight, Dustproof, Crushproof
- Specialized laptop and
- organization solutions
- Micro Case protection for small electronics Lockable
- Automatic pressure regulation
- Lifetime guarantee

# FLASHLIGHTS

Pelican Products, Inc. guarantees its products for a lifetime against breakage or defects in workmanship. This guarantee does not cover the lamp or batteries (rechargeable or alkaline). All warranty claims of any nature are barred if the flashlight has been altered, damaged or in any way physically changed, or subjected to abuse, misuse, negligence or accident. Refer to www.pelican.com/warranty for full details.

### AALG PRODUCTS

Pelican guarantees its AALG products for 1 year against defects in materials and workmanship from the date of purchase. All warranty claims of any nature are barred if the product has been altered, damaged or in any way physically changed, or subjected to abuse, misuse, negligence or accident. Refer to www.pelican.com/warranty for full details.

Refer to www.pelican.com/warranty for full details of Pelican warranties.

©2011 Pelican Products, Inc. All trademarks are registered and/o unregistered trademarks of Pelican Products, Inc., its subsidiaries and/or affiliates. iPad is a registered trademark of the Apple Inc.



# 



# **////** SPECIALTY PRODUCTS



# Portable workspace solutions that deploy

- Storage chest with metal rawers and dividers to keep supplies safe and organize
- Rack Case protectio for servers and computer
- Footlocker and Trunk Locker Storag
- Protection for oxygen tanks

#### APPLICATION:

Field Desks eld hospitals and check-in points

#### Rack Cases

uperior protection for tra ommand center control quipment in remote environm

- Foot Lockers and Trunk Lockers Store and transport bedding olankets, clothes, food, wate
- Medical Chests Various items, small tools and medical supplies for field hospitals

APPLICATION:

Search & rescue onerat

Search & rescue operation
Security checkpoints

Power outages



# **////** RALS | REMOTE AREA LIGHTS

### • Up to \*15 hours of light

- Lightweight
- Battery powe
- Advanced LED technolo
- Portable
- Silent
- Rechargeable
- Collapsible mast

- Dustproof, crushproof water res
- Automatic pre
- Specialized laptop ar

# APPLICATION:

- First aid supplies
- *Nonitors, displays, projectors*
- Search & rescue operations
- Dxygen tanks
- light vision equipme

- Automated external defibrillatorsDive bags



# **//** TOUGH LIGHTING TOOLS



- Safety approved lights for hazardous areas
- Specialized lights for fire and rescue operation
- lights for diving
- Headlights
- LED Technolog

# APPLICATION:

- Power outa
- Distress sign
- escue operatio
- ndividuals and pets
- Emergency preparedness kit

- **/////** EMS AND TRANSPORT CASES





# ///// PRODUCT SPECIFICATIONS

	HAND-HELD/H	AND-HELD/HANDS FREE LIGHTS						
		BATTERIES			ANSI LIGHT OUTPUT	ANSI RUNTIME	APPROVALS	
8	2220 LED	2 CR2032 Lithium*	1 oz. (0.03 kg)	3.5" (8.9 cm)	9	34h	CI D1	
ŝ	1830 LED	3 AAAA Alkaline*	1.2 oz. (0.03 kg)	6.2" (15.7 cm)	5	32h	CI D1	
	1910 LED	1 AAA Alkaline*	1.4 oz. (0.04 kg)	3.6" (9.1 cm)	39	1h	N/A	
	1920 LED	2 AAA Alkaline*	2.2 oz. (0.06 kg)	5.3" (13.5 cm)	67	2h 45m	N/A	
	2000	3 C Alkaline	12.8 oz. (0.36 kg)	7.79" (19.8 cm)	53	5h	CI D2	
	2010 Recoil <sup>™</sup> LED	3 C Alkaline	13.4 oz. (0.38 kg)	8.11" (20.6 cm)	56	43h	CI II III D1	
	2400	4 AA Alkaline*	7.1 oz. (0.2 kg)	6.49" (16.5 cm)	45	3h 45m	CI D1	
	2410 Recoil <sup>™</sup> LED	4 AA Alkaline*	7.3 oz. (0.21 kg)	7" (17.8 cm)	72	7h 15m	CI II III D1	
	2610 LED	3 AAA Alkaline*	3.2 oz. (0.09 kg)	1.49" (3.8 cm)	30 (high) 14 (low)	19h (high), 47h (low)	CI D1	
	2620 LED	3 AAA Alkaline*	4.8 oz. (0.14 kg)	2.16" (5.5 cm)	26 (high) 14 (low)	2h 15m (high), 18h (low)	CI D1	
	2690 LED	3 AAA Alkaline*	4.1 oz. (0.12 kg)	2.81" (7.1 cm)	60	10h 30m	CI II III D1	
	3330 LED	2 CR123 Lithium*	3.45 oz. (0.1 kg)	5.27" (13.4 cm)	90	4h 45m	N/A	
	3610 Recoil <sup>™</sup> LED	4 AA Alkaline*	10.5 oz. (0.3 kg)	7.51" (19.1 cm)	72	7h 15m	CI II III D1	
	3700	4 C Alkaline	20.32 oz. (0.58 kg)	7" (17.8 cm)	39 (high) 25 (backup)	6h 15m (high), 8h 30m (backup)	CI D2	
K	9410 LED Lantern	Rechargeable Ni-MH*	49.28 oz. (1.4 kg)	8.75" (22.2 cm)	741 (high) 300 (low)	1h 45m (high), 4h 45m (low)	N/A	
6	100 M	* Batteries Included	* With Batteries	1000	-		CEDA DE	

CASES	INTERIOR DIMENSIONS		EXTERIOR DIMENSIONS				
MICRO CASES	INCHES	CENTIMETERS	INCHES	CENTIMETERS			
1015	5.14" x 2.64" x 1.37"	(13.1 x 6.7 x 3.5) (16.2 x 6.7 x 5.2)	6.68" x 3.88" x 1.86"	(17 x 9.9 x 4.7) (19 x 9.8 x 6.2)			
1030	6.37" x 2.62" x 2.06"		7.50" x 3.87" x 2.43"				
1040	6.50" x 3.87" x 1.75"	(16.5 x 9.8 x 4.4)	7.50" x 5.06" x 2.12"	(19 x 12.8 x 5.4)			
TABLET   NETBOOK   LAPTOP CASES							
1055 (fits 7" Tablets and eBook Readers)	8.55" x 5.52" x 0.85"	(21.7 x 14 x 2.2 cm)	9.42" x 7.02" x 1.24"	(23.9 x 17.8 x 3.1 cm)			
1065 (fits iPads and 10" Tablets)	9.96" x 7.76" x 0.97"	(25.3 x 19.7 x 2.5 cm)	10.86" x 9.28" x 1.24"	(27.6 x 23.6 x 3.1 cm)			
1075* (fits iPads, netbooks, and 10.1" tablets)	11.11" x 7.92" x 1.63"	(28.2 x 20.1 x 4.1 cm)	12.38" x 9.75" x 2.13"	(31.4 x 24.8 x 5.4)			
1085* (fits 14" Laptops)	14.29" x 10.37" x 1.97	(36.3 x 26.3 x 5 cm)	15.64" x 12.41" x 2.50"	(39.7 x 31.5 x 6.3 cm)			
1095* (fits 15.6" Laptops)	15.78" x 11.16" x 2.06"	(40.1 x 28.3 x 5.2 cm)	17.18" x 13.24" x 2.6"	(43.6 x 33.6 x 6.6 cm)			
1495 (fits up to 17" Laptops)	18.87" x 13.12" x 3.81"	(47.9 x 33.3 x 9.7 cm)	21.62" x 17.25" x 4.87"	(54.9 x 43.8 x 12.4 cm)			
* Shoulder Strap Included		CALCULATION OF		NO IN COMPANY			
TRANSPORT CASES							
iM2075	9.50" x 7.50" x 7.25"	(24.1 x 19 x 18.4)	11.80" x 9.80" x 7.70"	(30 x 24.9 x 19.6)			
1450	14.62" x 10.18" x 6.00"	(37.1 x 25.8 x 15.2)	16.00" x 13.00" x 6.87"	(40.6 x 33 x 17.4)			
1510	19.75" x 11.00" x 7.60"	(50.1 x 27.9 x 19.3)	22.00" x 13.81" x 9.00"	(55.9 x 35.1 x 22.9)			
1620	21.48" x 16.42" x 12.54"	(54.5 x 41.7 x 31.8)	24.64" x 19.39" x 13.78"	(62.6 x 49.2 x 35)			
iM2750	22.00" x 17.00" x 12.70"	(55.9 x 43.2 x 32.2)	24.60" x 19.70" x 14.40"	(62.5 x 50 x 36.6)			
0500	34.95" x 18.45" x 25.25"	(88.7 x 46.8 x 64.1)	39.95" x 23.45" x 28.65"	(101.4 x 59.5 x 72.7)			
EMS CASES							
1460 EMS	18.54" x 9.92" x 10.92"	(47.1 x 25.2 x 27.7)	20.85" x 12.73" x 12.75"	(52.9 x 32.3 x 32.4)			
1500 EMS	16.75" x 11.18" x 6.12"	(42.5 x 28.4 x 15.5)	18.50" x 14.06" x 6.93"	(47 x 35.7 x 17.6)			
1550 EMS	18.43" x 14.00" x 7.62"	(46.8 x 35.5 x 19.3)	20.62" x 16.87" x 8.12"	(52.4 x 42.8 x 20.6)			
1600 EMS	21.43" x 16.50" x 7.87"	(54.4 x 41.9 x 20)	24.25" x 19.43" x 8.68"	(61.6 x 49.3 x 22)			
SPECIALTY PRODUCTS							
0450 Mobile Tool Chest	20.56" x 10.97" x 12.65"	(52.2 x 27.9 x 32.1)	23.95" x 14.75" x 17.95"	(60.8 x 37.5 x 45.6)			
1460 Mobile Tool Chest	18.54" x 9.92" x 10.92"	(47.1 x 25.2 x 27.7 cm)	20.85" x 12.73" x 12.75"	(52.9 x 32.3 x 32.4 cm)			
472-Tank-D-2-032	N/A	N/A	26.00" x 14.70" x 5.50"	(66.04 x 37.34 x 13.97)			
472-MEDCHEST3-4D-032	N/A	N/A	32.75" x 20.87" x 12.61"	(83.2 x 53 x 32)			
472-FLD-DESK-TA-032	N/A	N/A	30.70" x 21.00" x 28.50"	(77.9 x 53.3 x 72.4)			
Rack Case	Rack case size availability: 3U to	26U					

	RALS	BATTERIES*	WEIGHT*	LENGTH*	LUMENS	RUNTIME	BEAM SPREAD	LEDs	HEADS	APPROVALS
8	9430	Rechargeable, Sealed	22.5 lbs. (10 kg)	32.28" (82 cm)	2000 (high) 1000 (low)	8h (high), 15h (low)	90°	24 per head	1	N/A
	9435	Rechargeable NiMH	17.6 lbs. (7.98 kg)	32.28" (82 cm)	1500 (high) 750 (low)	5h (high), 10h (low)	90°	18 per head	1	CI D2
l	9460	Rechargeable, Sealed	50.71 lbs. (23 kg)	70.87" (179.9 cm)	4000 (high) 2000 (low)	7h (high), 14h (low)	90°	24 per head	2	N/A
ŝ	9470	Rechargeable, Sealed	88.18 lbs. (40 kg)	72.85" (185 cm)	8000 (high) 4000 (low)	7h (high), 14h (low)	90°	24 per head	4	N/A
ş	9440	Rechargeable NiMH	16.09 lbs. (7.3 kg)	86.25" (219 cm)	2400 (high) 1200 (low)	3h (high), 6h (low)	120°	10 per head	1	N/A
	100 million (100 million)	* Batteries Included	* With Batteries	* Extended Height	No. of Concession, Name		and the second se	and the second second		