PELICAN LEGENDARY LIFETIME GUARANTEE OF EXCELLENCE

Pelican Products, Inc. guarantees its products for a lifetime against breakage or defects in workmanship. Pelican[™] injection molded cases are guaranteed to be watertight to a depth of 3.3 feet (1 meter) for 30 minutes (IP 67) if properly closed with undamaged o-ring in place unless otherwise stated. Pelican's liability is limited to the case and not its contents or foam. All warranty claims of any nature are barred if the container has been altered, damaged or in any way physically changed, or subjected to abuse, misuse, negligence or accident. Refer to www.pelican.com/warranty for full details.

Lifetime Guarantee does not cover Roto Molded or AALG products. Refer to www.pelican.com/warranty for full details.

U.S.A.

TO ORDER PELICAN LIGHTS AND CASES IN THE USA:

CALIFORNIA

23215 Early Avenue Torrance, CA 90505 Tel: 310.326.4700 800.473.5422 Fax: 310.326.3311 www.pelican.com MASSACHUSETTS 147 North Main Street South Deerfield, MA 01373 Tel: 800.542.7344 Fax: 413.665.8330

www.pelican.com

TO ORDER PELICAN STORM OR PELICAN HARDIGG CASES IN THE USA:

INDIANA 3802 N 600 W # B Greenfield, IN 46140-9642 Tel: 317.866.2040

www.pelican.com

INTERNATIONAL

CANADA

Pelican Products, Inc. 10221-184th Street Edmonton, Alberta T5S 2J4 Canada Tel: 780.481.6076 Fax: 780.481.9586 www.pelican.ca

CHINA

Pelican Products China Representative Office Pine City Building, Room 1026 777 Zhaojiabang Road Shanghai, China 200032 Tel +86.21.64189685 Fax +86.21.64189679 www.pelican.com/cn

EUROPE, MIDDLE EAST & AFRICA Peli Products, S.L.U. c/ Provença, 388, Planta 7 08010 • Barcelona, Spain Tel +34 93 467 4999 Fax +34 93 487 7393 www.peli.com

JAPAN Pelican Products K.K.

Nisso 22 Bldg. 9F 1-11-10 Azabu Dai Minato Ward Tokyo 106-0041 Japan Tel +81 33 585 9100 Fax +81 33 585 9109 www.pelicanproducts.jp

AUSTRALIA

Pelican Products Pty Ltd Suite 2.33, Platinum West 4 Ilya Avenue, Erina NSW 2250 Australia Ph: +612 4367 7022 Fax: +612 4367 7066 www.pelicanaustralia.com

DISTRIBUTED BY:





©2011 Pelican Products, Inc. All trademarks are registered and/or unregistered trademarks of Pelican Products, Inc., its subsidiaries and/or affiliates. Part No. 0030-000-900 AP_11

PELICAN



FULL LINE BROCHURE



You've got equipment to protect, and a Pelican Storm Case is the best way to do it. Why? It's all about the resin: our proprietary HPX® polymer is proven to resist impacts even in low-temperature laboratory testing. But the real proof is in the bragging rights that come with survival. Because

to a Pelican Storm Case, whether falling from a helicopter, crashing down class V rapids or taking a hit in the center lane of the New Jersey turnpike is all in a day's work.



Press & Pull[®] Latches

These smooth-opening, dependable, patented latches hold tight under pressure and impact despite fastopening performance. Tested to over 400 lbs., yet open with a simple release button.

Molded-In Lockable Hasps

Twin mating hasp holes on the rim of the case allow attachment of padlocks to keep your gear in and thieves out. And check out Pelican's TSA approved cable padlock. Now you can check your baggage with confidence while flying in the USA. The Travel Security Agency has the key, and you have the combination.

iM2300



iM2306

Rugged In-Line Wheels

Shielded from dust, dirt and other contaminants ball bearing wheels provide low-friction, low-drag rolling with retractable handles for easy movement of heavy loads. Look for the 40 icon for availability on select models.

Double-Layer, Soft-Grip Handles

When the weather goes south you'll find a secure grip that won't slip. An in-tool vulcanizing process over-molds the grips to the polymer handle for a



CAT #	Interior Dimensions*	Exterior Dimensions	Weight	Clrs	Pick N Phil	Padded Divided	Bezal	Lid Se	Telescopi	Wheele	Meets A:
M2050	9.5" L x 7.5" W x 4.25" H (24.1 x 19 x 10.8 cm)	11.8" L x 9.8" W x 4.7" H (30 x 24.9 x 11.9 cm)	2.7 lbs. (1.2 kg)		S	0	0	0			s
i M 2075	9.5" L x 7.5" W x 7.25" H (24.1 x 19 x 18.4 cm)	11.8" L x 9.8" W x 7.7" H (30 x 24.9 x 19.6 cm)	3.3 lbs. (1.5 kg)		S	0	0	0			S
i M 2100	13" L x 9.2" W x 6" H (33 x 23.4 x 15.2 cm)	14.2" L x 11.4" W x 6.5" H (36.1 x 28.9 x 16.5 cm)	4.2 lbs. (1.9 kg)		S	0	0	0			S
M2200	15" L x 10.5" W x 6" H (38.1 x 26.7 x 15.2 cm)	16.2" L x 12.7" W x 6.6" H (41.1 x 32.2 x 16.8 cm)	4.9 lbs. (2.2 kg)		S	0	0	0			S
i M 2300	17" L x 11.7" W x 6.2" H (43.2 x 29.7 x 15.7 cm)	18.2" L x 13.4" W x 6.7" H (46.2 x 34 x 17 cm)	5.8 lbs. (2.6 kg)		S	0	0	0			S
i M 2306	17" L x 6.3" W x 6.2" H (43.2 x 16 x 15.7 cm)	18.2" L x 8.4" W x 6.7" H (46.2 x 21.3 x 17 cm)	4.3 lbs. (2.0 kg)		S	ο	0	0			S
M2370	18.2" L x 12.1" W x 5.2" H (46.2 x 30.7 x 13.2 cm)	20" L x 14.7" W x 5.8" H (50.8 x 37.3 x 14.7 cm)	5.7 lbs. (2.6 kg)		S	0	0	0			S
i M 2400	18" L x 13" W x 6.7" H (45.7 x 33 x 17 cm)	19.2" L x 15.2" W x 7.3" H (48.7 x 38.6 x 18.5 cm)	6.5 lbs. (3.0 kg)		S	0	ο	ο			s
i M 2450	18" L x 13" W x 8.4" H (45.7 x 33 x 21.3 cm)	19.2" L x 15.2" W x 9" H (48.7 x 38.6 x 22.9 cm)	7.4 lbs. (3.4 kg)		S	0	0	0			s
i M 2500	20.5" L x 11.5" W x 7.2" H (52 x 29.2 x 18.3 cm)	21.7" L x 14.1" W x 8.9" H (55.1 x 35.8 x 22.6 cm)	11 lbs. (5.0 kg)		S	0	0	0	S	s	s
i M 2600	20" L x 14" W x 7.7" H (50.8 x 35.5 x 19.6 cm)	21.2" L x 16" W x 8.3" H (53.8 x 40.6 x 21.1 cm)	8.5 lbs. (3.9 kg)		S	0	0	0			
i M 2620	20" L x 14" W x 10" H (50.8 x 35.5 x 25.4 cm)	21.2" L x 16" W x 10.6" H (53.8 x 40.6 x 26.9 cm)	12.5 lbs. (5.7 kg)		S	0	0	0	s	S	
i M 2700	22" L x 17" W x 8" H (55.9 x 43.2 x 20.3 cm)	24.6" L x 19.7" W x 8.6" H (62.5 x 50 x 21.8 cm)	11.1 lbs. (5.0 kg)		S	0	0	0			
i M 2720	22" L x 17" W x 10" H (55.9 x 43.2 x 25.4 cm)	24.6" L x 19.7" W x 11.7" H (62.5 x 50 x 29.7 cm)	16.8 lbs. (7.6 kg)		S	0	0	0	S	S	
i M 2750	22" L x 17" W x 12.7" H (55.9 x 43.2 x 32.2 cm)	24.6" L x 19.7" W x 14.4" H (62.5 x 50 x 36.6 cm)	18.5 lbs. (8.4 kg)		S	0	0	0	s	s	
i M 2875	22.5" L x 21.1" W x 11.4" H (57.1 x 53.6 x 28.9 cm)	24.9" L x 23.7" W x 13.1" H (63.2 x 60.2 x 33.3 cm)	20.1 lbs. (9.1 kg)		S	0	ο	0	s	s	
i M 2950	29" L x 18" W x 10.5" H (73.6 x 45.7 x 26.7 cm)	31.3" L x 20.4" W x 12.2" H (79.5 x 51.8 x 31 cm)	20.8 lbs. (9.5 kg)		S	0	0	0	S	S	
i M 2975	29" L x 18" W x 13.8" H (73.6 x 45.7 x 35 cm)	31.3" L x 20.4" W x 15.5" H (79.5 x 51.8 x 39.4 cm)	22.5 lbs. (10.2 kg)		S	0	0	0	S	S	
i M 3075	29.8" L x 20.8" W x 17.8" H (75.7 x 52.8 x 45.2 cm)	33.3" L x 24.4" W x 19.3" H (84.5 x 62 x 49 cm)	31.5 lbs. (14.3 kg)		S	0	0	0	S	S	
i M 3100	36.5" L x 14" W x 6" H (92.7 x 35.5 x 15.2 cm)	39.8" L x 16.5" W x 6.7" H (101.1 x 41.9 x 17 cm)	15.2 lbs. (6.9 kg)		S (standard), O (optional)						
i M 3200	44" L x 14" W x 6" H (111.7 x 35.5 x 15.2 cm)	47.2" L x 16.5" W x 6.7" H (119.8 x 41.9 x 17 cm)	17.7 lbs. (8.0 kg)		-**Available as add-on kits only. Require additional assembly S - All cases available with no foam as an option S - iM3100 through iM3300 come with multilayer foam S						
i M 3220	44" L x 14" W x 8.5" H (111.7 x 35.5 x 21.6 cm)	47.2" L x 16.5" W x 9.2" H (119.8 x 41.9 x 23.4 cm)	20.4 lbs. (9.3 kg)								
i M 3300	50.5" L x 14" W x 6" H (128.2 x 35.5 x 15.2 cm)	53.8" L x 16.5" W x 6.7" H (136.6 x 41.9 x 17 cm)	19 lbs. (8.6 kg)							s	

* Lid height included in interior dimensions: iM2050-iM2075 1.5 inch (3.8 cm) lid, iM2370 1.7 inch (4.3 cm) lid, iM3075 4 inch (10.2 cm) lid, iM2100-3300 2 inch (5.1 cm) lid









Vortex[®] Pressure Release Valve

The built-in technology of Pelican Storm Cases automatic pressure equalization valve is also a patented feature. Air travel prevents vacuum lock to make opening the case natural even after



extreme altitude changes. At the same time, the microscopic filter blocks water molecules and dust particles so your gear stays clean in the Gobi and dry on the Nile.